



Uncertain Data Management

Boolean c-tables

Antoine Amarilli¹, Silviu Maniu²

November 28th, 2016

¹Télécom ParisTech

²LRI

Remember **c-tables**:

Member \bowtie Booking

id	date	teacher	class	room	
2	2016-11-28	$NULL_1$	UDM	$NULL_2$	
3	2016-12-05	$NULL_1$	UDM	$NULL_2$	
4	2016-12-12	$NULL_1$	UDM	$NULL_2$	<i>if $NULL_0$ is "UDM"</i>

Remember **c-tables**:

Member \bowtie Booking

id	date	teacher	class	room
2	2016-11-28	NULL ₁	UDM	NULL ₂
3	2016-12-05	NULL ₁	UDM	NULL ₂
4	2016-12-12	NULL ₁	UDM	NULL ₂

if NULL₀ is "UDM"

→ **Variant**: Only allow NULLs in the **conditions**

NULLs in conditions

- The **possible tuples** are exactly the **rows**
- Each row may either be **kept** or **deleted**
 - Depends on the **condition**

NULLs in conditions

- The **possible tuples** are exactly the **rows**
 - Each row may either be **kept** or **deleted**
 - Depends on the **condition**
- **Finite** number of possible worlds

NULLs in conditions

- The **possible tuples** are exactly the **rows**
- Each row may either be **kept** or **deleted**
 - Depends on the **condition**
- **Finite** number of possible worlds
 - at most 2^N if we have N rows

Example

Member \bowtie Booking

id	date	teacher	class	room	
2	2016-11-28	Antoine	UDM	C42	if $NULL_1$ is "Antoine"
3	2016-12-05	Antoine	UDM	C42	if $NULL_1$ is "Antoine"
4	2016-12-12	Antoine	UDM	C42	if $NULL_1$ is "Antoine"
2	2016-11-28	Silviu	UDM	C42	if $NULL_1$ is "Silviu"
3	2016-12-05	Silviu	UDM	C42	if $NULL_1$ is "Silviu"
4	2016-12-12	Silviu	UDM	C42	if $NULL_1$ is "Silviu"

Table of contents

Definitions

Boolean c-tables

Expressiveness

Boolean c-tables

With **Boolean c-tables**, we impose:

- the possible values of each **NULL_i** are **True** and **False**

Boolean c-tables

With **Boolean c-tables**, we impose:

- the possible values of each **NULL_i** are **True** and **False**

We can **simplify notation**

- We write the **NULLs** as **Boolean variables** x_i
- We replace $x_i = \text{True}$ by just x_i
- We replace $x_i = \text{False}$ by $\neg x_i$

Boolean c-tables

With **Boolean c-tables**, we impose:

- the possible values of each **NULL_i** are **True** and **False**

We can **simplify notation**

- We write the **NULLs** as **Boolean variables** x_i
- We replace $x_i = \text{True}$ by just x_i
- We replace $x_i = \text{False}$ by $\neg x_i$
- We can **rewrite**:
 - $x_i = x_j$ to $(x_i \wedge x_j) \vee (\neg x_i \wedge \neg x_j)$
 - $x_i \neq x_j$ to $(x_i \wedge \neg x_j) \vee (\neg x_i \wedge x_j)$

Boolean c-tables

With **Boolean c-tables**, we impose:

- the possible values of each **NULL_i** are **True** and **False**

We can **simplify notation**

→ We write the **NULLs** as **Boolean variables** x_i

→ We replace $x_i = \text{True}$ by just x_i

→ We replace $x_i = \text{False}$ by $\neg x_i$

→ We can **rewrite**:

- $x_i = x_j$ to $(x_i \wedge x_j) \vee (\neg x_i \wedge \neg x_j)$

- $x_i \neq x_j$ to $(x_i \wedge \neg x_j) \vee (\neg x_i \wedge x_j)$

→ The conditions become **Boolean expressions**

Theorem

*We can always rewrite a c-table having **NULLS** only in conditions to a Boolean c-table.*

Theorem

*We can always rewrite a c-table having **NULLS** only in conditions to a Boolean c-table.*

Two steps:

1. We can pick the **NULLS** in a **finite domain**
2. We can rewrite any **finite domain** to **True** and **False**

Reducing to a finite domain

- We can choose among **infinitely many** values for the **NULLs**
- However, the values only appear in the **conditions**:
 - $NULL_i = NULL_j$
 - $NULL_i = "c"$
 - Boolean combinations

Reducing to a finite domain

- We can choose among **infinitely many** values for the **NULLs**
- However, the values only appear in the **conditions**:
 - $NULL_i = NULL_j$
 - $NULL_i = "c"$
 - Boolean combinations
- We call two assignments of values to **NULLs equivalent** if all conditions evaluate to the **same**

Reducing to a finite domain (example)

→ Call two assignments of values to **NULLs equivalent** if all conditions evaluate to the **same**.

Consider the following:

- $NULL_1 = NULL_2$
- $NULL_2 = "c"$

→ **E.g.:** The assignment (a, d) is **equivalent** to (b, d)

Reducing to a finite domain (example)

→ Call two assignments of values to **NULLs equivalent** if all conditions evaluate to the **same**.

Consider the following:

- $NULL_1 = NULL_2$
- $NULL_2 = "c"$

→ **E.g.:** The assignment (a, d) is **equivalent** to (b, d)

→ What are the possible **assignments**?

Reducing to a finite domain (example)

→ Call two assignments of values to **NULLs equivalent** if all conditions evaluate to the **same**.

Consider the following:

- $NULL_1 = NULL_2$
- $NULL_2 = "c"$

→ **E.g.:** The assignment (a, d) is **equivalent** to (b, d)

→ What are the possible **assignments**?

- (c, c)

→ true, true

Reducing to a finite domain (example)

→ Call two assignments of values to **NULLs equivalent** if all conditions evaluate to the **same**.

Consider the following:

- $NULL_1 = NULL_2$
- $NULL_2 = "c"$

→ **E.g.:** The assignment (a, d) is **equivalent** to (b, d)

→ What are the possible **assignments**?

- (c, c)
 - **true, true**
- (x, c) with $x \neq c$
 - **false, true**

Reducing to a finite domain (example)

→ Call two assignments of values to **NULLs equivalent** if all conditions evaluate to the **same**.

Consider the following:

- $NULL_1 = NULL_2$
- $NULL_2 = "c"$

→ **E.g.:** The assignment (a, d) is **equivalent** to (b, d)

→ What are the possible **assignments**?

- (c, c)
 - **true, true**
- (x, c) with $x \neq c$
 - **false, true**
- (x, x) with $x \neq c$
 - **true, false**

Reducing to a finite domain (example)

→ Call two assignments of values to **NULLs equivalent** if all conditions evaluate to the **same**.

Consider the following:

- $NULL_1 = NULL_2$
- $NULL_2 = "c"$

→ **E.g.:** The assignment (a, d) is **equivalent** to (b, d)

→ What are the possible **assignments**?

- (c, c)
 - **true, true**
- (x, c) with $x \neq c$
 - **false, true**
- (x, x) with $x \neq c$
 - **true, false**
- (y, x) with $x \neq c$ and $y \neq x$
 - **false, false**

Reducing to a finite domain (concluding)

- Consider all **constants** that appear: \mathcal{C}
- Consider N different values \mathcal{V} ,
where N is the number of **NULLs**

Reducing to a finite domain (concluding)

- Consider all **constants** that appear: \mathcal{C}
 - Consider N different values \mathcal{V} ,
where N is the number of **NULLs**
- Gives our **domain** $\mathcal{D} := \mathcal{C} \sqcup \mathcal{V}$

Reducing to a finite domain (concluding)

- Consider all **constants** that appear: \mathcal{C}
 - Consider N different values \mathcal{V} ,
where N is the number of **NULLs**
- Gives our **domain** $\mathcal{D} := \mathcal{C} \sqcup \mathcal{V}$

Lemma

*For any c-table with **NULLs** only in conditions,
its set of possible worlds is the same:*

- *under the standard semantics*
- *when **NULLs** range over the finite \mathcal{D} .*

Reducing to a finite domain (concluding)

- Consider all **constants** that appear: \mathcal{C}
 - Consider N different values \mathcal{V} ,
where N is the number of **NULLs**
- Gives our **domain** $\mathcal{D} := \mathcal{C} \sqcup \mathcal{V}$

Lemma

For any c -table with **NULLs** only in conditions,
its set of possible worlds is the same:

- *under the standard semantics*
 - *when **NULLs** range over the finite \mathcal{D} .*
- For **simplicity**, let's **pad** \mathcal{D}
to have exactly 2^k values for some k

Rewriting to Boolean variables

- The **domain** has size 2^k .

Rewriting to Boolean variables

- The **domain** has size 2^k .
- Write its **values** in **binary**
- Encode each **NULL_i** to variables x_i^1, \dots, x_i^k

Rewriting to Boolean variables

- The **domain** has size 2^k .
 - Write its **values** in **binary**
 - Encode each NULL_i to variables x_i^1, \dots, x_i^k
- Can we **translate** the conditions?

Rewriting to Boolean variables (example)

- $\text{NULL}_7 = 001$

Rewriting to Boolean variables (example)

- $\text{NULL}_7 = 001$

- $x_7^1 = 0$ and $x_7^2 = 0$ and $x_7^3 = 1$

Rewriting to Boolean variables (example)

- $\text{NULL}_7 = 001$

- $x_7^1 = 0$ and $x_7^2 = 0$ and $x_7^3 = 1$

- $\neg x_7^1 \wedge \neg x_7^2 \wedge x_7^3$

Rewriting to Boolean variables (example)

- $\text{NULL}_7 = 001$
 - $x_7^1 = 0$ and $x_7^2 = 0$ and $x_7^3 = 1$
 - $\neg x_7^1 \wedge \neg x_7^2 \wedge x_7^3$
- $\text{NULL}_7 \neq 001$

Rewriting to Boolean variables (example)

- $\text{NULL}_7 = 001$
 - $x_7^1 = 0$ and $x_7^2 = 0$ and $x_7^3 = 1$
 - $\neg x_7^1 \wedge \neg x_7^2 \wedge x_7^3$
- $\text{NULL}_7 \neq 001$
 - **negate** the above

Rewriting to Boolean variables (example)

- $\text{NULL}_7 = 001$
 - $x_7^1 = 0$ and $x_7^2 = 0$ and $x_7^3 = 1$
 - $\neg x_7^1 \wedge \neg x_7^2 \wedge x_7^3$
- $\text{NULL}_7 \neq 001$
 - **negate** the above
- $\text{NULL}_7 = \text{NULL}_8$

Rewriting to Boolean variables (example)

- $\text{NULL}_7 = 001$
 - $x_7^1 = 0$ and $x_7^2 = 0$ and $x_7^3 = 1$
 - $\neg x_7^1 \wedge \neg x_7^2 \wedge x_7^3$
- $\text{NULL}_7 \neq 001$
 - **negate** the above
- $\text{NULL}_7 = \text{NULL}_8$
 - $x_7^1 = x_8^1$ and $x_7^2 = x_8^2$ and $x_7^3 = x_8^3$

Rewriting to Boolean variables (example)

- $\text{NULL}_7 = 001$
 - $x_7^1 = 0$ and $x_7^2 = 0$ and $x_7^3 = 1$
 - $\neg x_7^1 \wedge \neg x_7^2 \wedge x_7^3$
- $\text{NULL}_7 \neq 001$
 - **negate** the above
- $\text{NULL}_7 = \text{NULL}_8$
 - $x_7^1 = x_8^1$ and $x_7^2 = x_8^2$ and $x_7^3 = x_8^3$
- $\text{NULL}_7 \neq \text{NULL}_8$

Rewriting to Boolean variables (example)

- $\text{NULL}_7 = 001$
 - $x_7^1 = 0$ and $x_7^2 = 0$ and $x_7^3 = 1$
 - $\neg x_7^1 \wedge \neg x_7^2 \wedge x_7^3$
- $\text{NULL}_7 \neq 001$
 - **negate** the above
- $\text{NULL}_7 = \text{NULL}_8$
 - $x_7^1 = x_8^1$ and $x_7^2 = x_8^2$ and $x_7^3 = x_8^3$
- $\text{NULL}_7 \neq \text{NULL}_8$
 - **negate** the above

Concluding

- We have moved to a **finite domain**
(without changing the table)

Concluding

- We have moved to a **finite domain**
(without changing the table)
- We have **rewritten** to Boolean variables
(we changed the table)

Concluding

- We have moved to a **finite domain**
(without changing the table)
- We have **rewritten** to Boolean variables
(we changed the table)
- It **suffices** to study Boolean c-tables

Table of contents

Definitions

Boolean c-tables

Expressiveness

Strong representation system

- Are Boolean c-tables a **strong representation system** for relational algebra? ...

Strong representation system

- Are Boolean c-tables a **strong representation system** for relational algebra? ...
 - **Yes!**

Strong representation system

- Are Boolean c-tables a **strong representation system** for relational algebra? ...
 - **Yes!**
 - **c-tables** are
 - **NULLs** will never **appear** by themselves outside of conditions

Capturing all uncertain relations

- Fix a set of **possible tuples**
- A **possible world**: a subset of the **possible tuples**
- An **uncertain relation**: set of **possible worlds**

Capturing all uncertain relations

- Fix a set of **possible tuples**
- A **possible world**: a subset of the **possible tuples**
- An **uncertain relation**: set of **possible worlds**

Booking			Booking		
date	teacher	room	date	teacher	room
21	Antoine	Saphir	21	Antoine	Saphir
21	Silviu	Saphir	21	Silviu	Saphir
21	Silviu	C47	21	Silviu	C47
28	Antoine	Saphir	28	Antoine	Saphir
28	Antoine	C47	28	Antoine	C47
28	Silviu	Saphir	28	Silviu	Saphir

Capturing all uncertain relations

- Fix a set of **possible tuples**
- A **possible world**: a subset of the **possible tuples**
- An **uncertain relation**: set of **possible worlds**

Booking			Booking		
date	teacher	room	date	teacher	room
21	Antoine	Saphir	21	Antoine	Saphir
21	Silviu	Saphir	21	Silviu	Saphir
21	Silviu	C47	21	Silviu	C47
28	Antoine	Saphir	28	Antoine	Saphir
28	Antoine	C47	28	Antoine	C47
28	Silviu	Saphir	28	Silviu	Saphir

→ Can we capture all **uncertain relations**?

Capturing uncertain relations

- Make multiple **copies** of possible worlds so there are 2^k possible worlds
- Write each **possible world** in binary

Capturing uncertain relations

- Make multiple **copies** of possible worlds so there are 2^k possible worlds
- Write each **possible world** in binary

00		01		10	
v	w	v	w	v	w
a	d	a	d	a	d
b	e	b	e	b	e
c	f	c	f	c	f

Capturing uncertain relations

- Make multiple **copies** of possible worlds so there are 2^k possible worlds
- Write each **possible world** in binary

00		01		10		11	
v	w	v	w	v	w	v	w
a	d	a	d	a	d	a	d
b	e	b	e	b	e	b	e
c	f	c	f	c	f	c	f

Numbering tuples

For each **tuple**, write the **possible worlds** where it appears

Numbering tuples

For each **tuple**, write the **possible worlds** where it appears

00		01		10		11	
v	w	v	w	v	w	v	w
a	d	a	d	a	d	a	d
b	e	b	e	b	e	b	e
c	f	c	f	c	f	c	f

Numbering tuples

For each **tuple**, write the **possible worlds** where it appears

00		01		10		11	
v	w	v	w	v	w	v	w
a	d	a	d	a	d	a	d
b	e	b	e	b	e	b	e
c	f	c	f	c	f	c	f

v	w				
a	d	00	01	10	11
b	e		01		
c	f		01	10	11

Making a condition

- Create one **non-Boolean variable**
 - chooses the world
- Obtain a **non-Boolean** c-table

Making a condition

- Create one **non-Boolean variable**
 - chooses the world
- Obtain a **non-Boolean** c-table

v	w				
a	d	00	01	10	11
b	e		01		
c	f		01	10	11

Making a condition

- Create one **non-Boolean variable**
 - chooses the world
- Obtain a **non-Boolean** c-table

v	w				
a	d	00	01	10	11
b	e		01		
c	f		01	10	11

v	w	
a	d	$x = 00 \vee x = 01 \vee x = 10 \vee x = 11$
b	e	$x = 01$
c	f	$x = 01 \vee x = 10 \vee x = 11$

Making a Boolean c-table

Use the **previous trick** to rewrite to a **Boolean c-table**

Making a Boolean c-table

Use the **previous trick** to rewrite to a **Boolean c-table**

v	w	
a	d	$x = 00 \vee x = 01 \vee x = 10 \vee x = 11$
b	e	$x = 01$
c	f	$x = 01 \vee x = 10 \vee x = 11$

Making a Boolean c-table

Use the **previous trick** to rewrite to a **Boolean c-table**

v	w	
a	d	$x = 00 \vee x = 01 \vee x = 10 \vee x = 11$
b	e	$x = 01$
c	f	$x = 01 \vee x = 10 \vee x = 11$

v	w	
a	d	$\neg x_1 \wedge \neg x_2 \vee \neg x_1 \wedge x_2 \vee x_1 \wedge \neg x_2 \vee x_1 \wedge x_2$
b	e	$\neg x_1 \wedge x_2$
c	f	$\neg x_1 \wedge x_2 \vee x_1 \wedge \neg x_2 \vee x_1 \wedge x_2$

Conclusion

We have studied:

- First:
 - Codd tables with NULLS
 - v-tables with named NULLS
 - c-tables with named NULLS and conditions

Conclusion

We have studied:

- **First:**
 - Codd tables with NULLS
 - v-tables with named NULLS
 - c-tables with named NULLS and conditions
- **Then:**
 - c-tables with NULLS only in conditions
 - **Boolean** c-tables: Boolean variables

Conclusion

We have studied:

- First:
 - Codd tables with NULLS
 - v-tables with named NULLS
 - c-tables with named NULLS and conditions
- Then:
 - c-tables with NULLS only in conditions
 - Boolean c-tables: Boolean variables

We have shown:

- Any c-table with NULLS only in conditions **rewrites** to a Boolean c-table
- Boolean c-tables **capture** all finite uncertain tables
- Boolean c-tables are a **strong representation system**
- c-tables are a **strong representation system**

References I

 Abiteboul, S., Hull, R., and Vianu, V. (1995).

Foundations of Databases.

Addison-Wesley.

<http://webdam.inria.fr/Alice/pdfs/all.pdf>.

 Suciu, D., Olteanu, D., Ré, C., and Koch, C. (2011).

Probabilistic Databases.

Morgan & Claypool.

Unavailable online.